

		AJ 275-12-S	AJ 350-24-S	AJ 400-48-S	AJ 500-12-S	AJ 600-24-S	AJ 700-48-S	AJ 1000-12-S	AJ 1300-24-S	AJ 2100-12-S	AJ 2400-24-S	
Optionen												
Solarladeregler	Spannung max.	25 Vdc	45 Vdc	90 Vdc	25 Vdc	45 Vdc	90 Vdc	25 Vdc	45 Vdc	25 Vdc	45 Vdc	
	Ladestrom max.	10 Adc			15 Adc			25 Adc		30 Adc		
	Prinzip	3 Stufen (I/U/Uo) Schwebeladung										
	Absorptionsspannung	14.4 Vdc	28.8 Vdc	57.6 Vdc	14.4 Vdc	28.8 Vdc	57.6 Vdc	14.4 Vdc	28.8 Vdc	14.4 Vdc	28.8 Vdc	
	Schwebeladungs-spannung	13.6 Vdc	27.2 Vdc	54.4 Vdc	13.6 Vdc	27.2 Vdc	54.4 Vdc	13.6 Vdc	27.2 Vdc	13.6 Vdc	27.2 Vdc	
Eingang für Fernsteuerung (RCM)		•	•	•	•	•	•	•	•	•	•	
Zubehör												
Fernbedienung JT8								•				

* 120Vac/60Hz auf Anfrage

** Stand-by nur mit Option -S

Änderungen vorbehalten